



KERAFLEX MAXI S1
Declaration of Performance
No CPR-NO1/0466

DECLARATION OF PERFORMANCE No CPR-NO1/0466

- 1) Unique identification code of the product-type: **KERAFLEX MAXI S1**
- 2) Intended uses: **Improved cementitious adhesive for all internal and external tiling.**
- 3) Manufacturer: **Mapei AS - Vallsetvegen 6 - 2120 Sagstua - Norge (Norway) - www.mapei.no**
- 4) Harmonized standards: **EN 12004:2007+A1:2012**

No: Notified bodies:

0370 LGAI TECHNOLOGICAL CENTER, S. A.(Applus+)

0767 Kiwa MPA Dresden GmbH

- 5) Performances declared and Assessment and Verification of Constancy of Performance (AVCP):

Essential characteristics	Performances	AVCP
Reaction to fire:	Class A2_{FL}-s1/ A2-s1,d0	3
Bond strength:	expressed as: - initial tensile adhesion strength $\geq 1,0$ N/mm²	3
Durability of bond strength against: - climate/heat ageing action: - water/humidity action: - freeze-thaw cycles:	expressed as: - tensile adhesion strength after heat ageing $\geq 1,0$ N/mm² - tensile adhesion strength after water immersion $\geq 1,0$ N/mm² - tensile adhesion strength after freeze-thaw cycles $\geq 1,0$ N/mm²	3
Release of dangerous substances:	NPD	-

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.



KERAFLEX MAXI S1
Declaration of Performance
No CPR-NO1/0466

Signed for and on behalf of the manufacturer by: **Trond Hagerud – General Manager**

Sagstua, 28/09/2026

A handwritten signature in black ink, appearing to read "Hagerud", positioned above a dotted line.

The DoP in PDF format are available on our website.

<i>Revision 10 notes:</i>	<i>General update after the adoption of new software.</i>
---------------------------	---

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) No 1907/2006 and following amendments are indicated in the Safety Data Sheet that the manufacturer makes available on the website along with this current Declaration of Performance.

 0370, 0767	 Vallsetvegen 6 - 2120 Sagstua - Norge (Norway) www.mapei.no
23 CPR-NO1/0466 EN 12004 KERAFLEX MAXI S1 Improved cementitious adhesive for all internal and external tiling.	
Reaction to fire:	Class A2 _{FL} -s1/ A2-s1,d0
Bond strength:	expressed as: - initial tensile adhesion strength $\geq 1,0$ N/mm ²
Durability of bond strength against:	expressed as:
- climate/heat ageing action:	- tensile adhesion strength after heat ageing $\geq 1,0$ N/mm ²
- water/humidity action:	- tensile adhesion strength after water immersion $\geq 1,0$ N/mm ²
- freeze-thaw cycles:	- tensile adhesion strength after freeze-thaw cycles $\geq 1,0$ N/mm ²

The manufacturer supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.